



Minimum P.P.E requirements to be worn during installation:  
 Hard Hats, Glasses, Gloves, Boots, High Visibility Clothing  
 Minimum requirements for ALL sign placement  
 please follow instructions below without exception

- Minimum height 2.2m over footpath
- Minimum height 2.5m over cyclepath
- Minimum sideways clearance carriageway/Footpath 450mm
- Frames keep 1m clearance on footpath
- All frames must be sandbagged

Any issues not allowing you to follow regulations  
 please contact the office or out of hours.

TITLE / LOCATION		ADDRESS OF EVENT / TM		REF NUMBER:	
<b>Friargate LX</b>		<b>Cartergate, Grimsby, DN31 1QZ</b>		<b>NR0470</b>	
Plans Valid for Duration of Event	NOTES	DESIGNED BY	APPROVED BY	PLANNING NO:	
<input checked="" type="checkbox"/> DATE SIGNS ERRECTED		INITIALS DATE	INITIALS DATE	www.traffic.org.uk, info@traffic.org.uk	
<input checked="" type="checkbox"/> DATE OF EVENT / TM		AB 22-01-2018	MB 22-01-2018	1 of 1	
<input checked="" type="checkbox"/> SIGNS OUT FROM CAD OFFICE		CAD BY	UPDATED BY		
		INITIALS DATE	INITIALS DATE		
		AB 22-01-2018	AB 22-01-2018		



Traffic Management Services Ltd  
 Aurillac Way, Retford, Notts, DN22 7PX  
 Tel: 01777 705053, Fax: 01777 709878  
 www.traffic.org.uk, info@traffic.org.uk