



Minimum P/E requirements to be worn during installation:  
 Head Bands, Goggles, Gloves, Boots High Visibility Clothing  
 Minimum requirements for ALL sign placement:  
 P/E ratio of 10:1  
 Minimum height 2.2m over footpath  
 Minimum height 2.5m over cyclepath  
 Minimum sideways clearance  
 Carriageway/roadwidth 4.60m footpath  
 All frames must be sandbagged!  
 All frames must be sandbagged!  
 Any issues not allowing you to follow regulations please contact the office or out of hours.

**TITLE:**  
 Garden Street LX

**ADDRESS:**  
 Garden Street, Grimsby, DN32 0RH

Perme Valid for Duration of Event	
<b>DATE SIGNS ERECTED</b>	X
<b>DATE OF EVENT / TM</b>	X
<b>SIGNS OUT FROM CAD OFFICE</b>	28

DESIGNED BY		APPROVED BY	
INITIALS	DATE	INITIALS	DATE
AB	02-01-2018	LHT	02-01-2018
CAD BY		UPLOADED BY	
INITIALS	DATE	INITIALS	DATE
AB	02-01-2018	AB	02-01-2018

TRAFFIC MANAGEMENT SERVICES LTD	
Aunlic Way, Retford, Notts, DN22 7PX	
Tel: 01777 705053, Fax: 01777 708878	
www.traffic.org.uk, info@traffic.org.uk	

**TMS**

Traffic Management Services Ltd  
 Aunlic Way, Retford, Notts, DN22 7PX  
 Tel: 01777 705053, Fax: 01777 708878  
 www.traffic.org.uk, info@traffic.org.uk

**REF NUMBER:**  
 NR0405

**PLAN NO:**  
 1 of 1