



Minimum P.P.E requirements to be worn during installation:
 Hard Hats, Glasses, Gloves, Boots, High Visibility Clothing
 Minimum requirements for ALL sign placement
 please follow instructions below without exception

- Minimum height 2.2m over footpath
- Minimum height 2.5m over cyclepath
- Minimum sideways clearance
 carriageway/Footpath 450mm
- Frames keep 1m clearance on footpath
- All frames must be sandbagged

Any issues not allowing you to follow regulations
 please contact the office or out of hours.

TITLE / LOCATION		ADDRESS OF EVENT / TM			
Little London		A1173, Stallingborough, Grimsby, DN41 8BN			
Plans Valid for Duration of Event	NOTES	DESIGNED BY	DATE	APPROVED BY	DATE
DATE SIGNS ERCTED		INITIALS		INITIALS	
X		AB	29-09-2017	IR	02-10-2017
DATE OF EVENT / TM		CAD BY		UPDATED BY	
X		INITIALS	DATE	INITIALS	DATE
X	SIGNS OUT FROM CAD OFFICE	AB	29-09-2017	AB	29-09-2017
				 Traffic Management Services Ltd Aurillac Way, Retford, Notts, DN22 7PX Tel: 01777 705053, Fax: 01777 709878 www.traffic.org.uk, info@traffic.org.uk	
				REF NUMBER:	NR0008
				PLAN NO:	1 of 1